

Flood Risk Management Glossary

Term	Definition
Accretion	Accumulation of sediment.
Actions	Activities undertaken to reduce the impact of flooding.
	Actions describe where and how flood risk will be managed. These actions have been set by SEPA and agreed with flood risk management authorities.
	The actions presented in the consultation are draft and will be finalised after the consultation.
	Selection of actions to deliver the agreed objectives has been based on a detailed assessment and comparison of economic, social and environmental criteria.
Annual Average Damages (AAD)	Depending on its size or severity each flood will cause a different amount of damage to a given area.
	Annual Average Damages are the theoretical average economic damages caused by flooding when considered over a very long period of time.
	It does not mean that damage will occur every year: in many years there will be no damages, in some years minor damages and in a few years major damages may occur.
	High likelihood events, which occur more regularly, contribute proportionally more to AADs than rarer events.
	Within the flood risk management plans AADs incorporate economic damages to the following receptors: residential properties, non-residential properties, vehicles, emergency services, agriculture and roads. They have been

	calculated based on the principles set out in
	the Flood Hazard Research Centre Multi-Coloured Handbook (2010).
Appraisal	Appraisal is the process of defining objectives, examining options and weighing up costs, benefits, risks and uncertainties before a decision is made.
	The flood risk management plans appraisal method is designed to set objectives and identify the most sustainable combination of actions to tackle flooding from rivers, the sea and surface water.
Awareness raising	Public awareness, participation and community support are essential components of sustainable flood risk management.
	SEPA and the responsible authorities have a duty to raise public awareness of flood risk. This is undertaken both individually and collaboratively by a range of organisations.
	Improved awareness of flood risk and actions that prepare individuals, homes and businesses for flooding can reduce overall impact.
Bathing waters	Bathing waters are classed as protected areas under Annex IV of the Water Framework Directive (WFD).
	There are 84 designated bathing waters in Scotland.
Benefit cost ratio (BCR)	A benefit cost ratio summarises the overall value for money of an action or project. It is expressed as the ratio of benefits to costs (both expressed as present value monetary values).
	A ratio of greater than 1:1 indicates that the economic benefits associated with an action are greater than the economic costs of implementation; therefore, this is taken as the threshold of economic viability.

	It should be acknowledged that it is not always possible to accurately estimate economic values for all elements of benefit, and BCR is just one of a number of techniques used in appraisal.
Blue infrastructure	Blue infrastructure is often complementary to 'green infrastructure' and includes sustainable drainage systems, swales (shallow, broad and vegetated channels designed to store and/or convey runoff and remove pollutants), wetlands, rivers, canals (and their banks) and all watercourses.
Business and services	Properties that are not used for people to live in, such as shops or other public, commercial or industrial buildings.
Catchment	All the land drained by a river and its tributaries.
Category 1 and 2 responders (Cat 1 / 2)	Category 1 and 2 Responders are defined as part of the Civil Contingencies Act 2004 which seeks to minimise disruption in the event of an emergency.
	Category 1 Responders are 'core' responders: local authorities, police, fire and rescue services, ambulance service, NHS health boards, SEPA and the Maritime and Coastguard Agency.
	Category 2 Responders are key co- operating responders in support of Category 1 Responders. These include gas and electricity companies, rail and air transport operators, harbour authorities, telecommunications providers, Scottish Water, the Health and Safety Executive and NHS National Services Scotland.
Channel improvement	Where work has been carried out on the river's channel allowing an increase in the volume of water it can carry.
Characterisation	Provides a description of the natural characteristics of catchments, coastlines and urban areas in terms of

	hydrology, geomorphology, topography and land use. It also includes the characterisation of existing levels of flood risk and existing flood risk management activity.
Coastal flooding	Flooding that results from high sea levels or a combination of high sea levels and stormy conditions. The term coastal flooding is used under the Flood Risk Management (Scotland) Act 2009, but in some areas it is also referred to as tidal flooding and covers areas such as estuaries and river channels that are influenced by tidal flows.
Combined sewer	Combined sewers transport sewage from homes and industry as well as carrying surface water runoff from gutters, drains and some highways. Heavy or prolonged rainfall can rapidly increase the flow in a combined sewer until the amount of water exceeds sewer capacity.
Combined sewer (overflow) (CSO)	Combined sewer overflows are purposely designed structures to ensure any excess water from sewerage systems is discharged in a controlled way and at a specific managed location.
Community facility	Within the flood risk management plans this term includes: Emergency Services (Police, Fire, Ambulance, Coastguard, and Mountain Rescue) Educational Buildings (crèche, nursery, primary, secondary, further, higher and special education premises) Healthcare facilities: hospitals, health centres and residential care homes.
Community flood action groups	Community flood action groups are community-based resilience groups which, on behalf of local residents and business, help to prepare for and minimise the effects of flooding.

	They reflect the interests of their local communities and may differ in composition and remit. There are over 60 groups already established in Scotland. The Scottish Flood Forum provides support for both new and existing groups.
Confluence	Where two or more rivers meet.
Conveyance	Conveyance is a measure of the carrying capacity of a watercourse.
	Increasing conveyance enables flow to pass more rapidly and reducing conveyance slows flow down. Both actions can be effective in managing flood risk depending on local conditions.
Cross Border Advisory Group (CBAG)	The Cross Border Advisory Group is a statutory group made up of representatives from the Environment Agency, SEPA, Scottish Water and the four lead local flood authorities located within the Solway Tweed River Basin District.
Cultural heritage site	Historic Environment Scotland maintains lists of buildings of special architectural or historic interest; these buildings are referred to as 'listed buildings'. The highest level of designation is a
	World Heritage Site. Other designations included in this assessment are scheduled monuments, gardens and designed landscapes, and battlefields.
Culvert	A pipe, channel or tunnel used for the conveyance of a watercourse or surface drainage water under a road, railway, canal or other obstacle.
Damages	Flood damages are categorised as direct or indirect i.e. as a result of the flood water itself, or subsequent knock-on effects.

	Damage to buildings and contents caused by flood water are an example of direct damages, whilst loss of industrial production, travel disruption or stress and anxiety are indirect.
	Some damages can be quantified in monetary terms, and others can only be described.
	The potential damages avoided by implementation of a flood risk management action are commonly referred to as the benefits of that action.
	When comparing the effectiveness of different actions, it is useful to consider estimated damages and damages avoided across the lifespan of the action.
	Within the flood risk management plans, a 100-year appraisal period has been used as standard. This allows costs, damages and benefits across this time frame to be compared in present value terms.
	Also see: 'Annual Average Damages'
Demountable defences	A temporary flood barrier is one that is only installed when the need arises, that is, when flooding is forecast. A demountable flood defence is a
	particular type of temporary defence that requires built-in parts and therefore can only be deployed in one specific location.
Deposition	A natural process leading to an accumulation of sediment on a riverbed, floodplain or coastline.
Economic impact	An assessment of the economic value of the positive and negative effects of flooding and/or the actions taken to manage floods.
Embankment	Flood embankments are engineered earthfill structures designed to contain high river levels or protect against coastal flooding.

	They are commonly grass-covered but may need additional protection against erosion by swiftly flowing water, waves or overtopping.
Emergency plans / response	Emergency response plans are applicable for all types of flooding.
	They set out the steps to be taken during flooding in order to maximise safety and minimise impacts where possible.
	Under the Civil Contingencies Act, Category 1 Responders have a duty to maintain emergency plans.
	Emergency plans may also be prepared by individuals, businesses, organisations or communities.
Environmental impact	A change in the environment as a result of an action or activity.
	Impacts can be positive or negative and may vary in significance, scale and duration.
Environmental Impact Assessment (EIA)	Environmental Impact Assessment (EIA) is a process which identifies the potential environmental impacts, both negative and positive, of a proposal.
Environmental sites / environmental designated areas/ environmentally designated sites	Areas formally designated for environmental importance, such as Sites of Special Scientific Interest (SSSI) Special Protection Area (SPA) or Special Areas of Conservation (SAC).
Episodic erosion	Erosion induced by a single event, such as a storm.
	Erosion A natural process leading to the removal of sediment from a river bed, bank, floodplain or coastline.
Estuarine surge attenuation	A reduction in the wave energy caused by storm surge.
	Breakwaters (barriers built out into the sea to protect a coast or harbour from the force of waves) or habitats such as saltmarsh can slow down and reduce the inland impact of storm surges (the

	rising of the sea due to wind and atmospheric pressure changes associated with storms), thereby reducing coastal flood risk.
Estuary	A coastal body of water usually found where a river meets the sea; the part of the river that is affected by tides.
Fault (fault line)	A break or fracture in the earth's crust as a result of the displacement of one side with respect to the other. In Scotland, the Great Glen Fault is a major geological fault line cutting diagonally across the Highlands from Fort William to Inverness.
Flash flood	A flood that occurs a short period of time after high intensity rainfall or a sudden snow melt. A sudden increase in the level and velocity of the water body is often characteristic of these events, leaving a short time for warning or actions.
Flashy watercourse	A 'flashy' river or watercourse has a short lag time (the delay between peak rainfall intensity and peak river discharge), high peak discharge, and quickly returns to average flow. Rivers with these characteristics can be prone to flooding and leave a short time for warning or actions.
Flood	In the terms of the Flood Risk Management Act, 'flood' means a temporary covering by water, from any source, of land not normally covered by water. This does not include a flood solely from a sewerage system, as a result of normal weather or infrastructure drainage. A flood can cause significant adverse
	impacts on people, property and the environment.
Flood bund	A constructed retaining wall, embankment or dyke designed to

	protect against flooding to a specified standard of protection.
Flood defence	Infrastructure, such as flood walls and embankments, intended to protect an area against flooding, to a specified standard of protection.
Flood extent	The area that has been affected by flooding or is at risk of flooding from one or more sources for a particular likelihood.
Flood forecasting	SEPA operates a network of over 250 rainfall, river and coastal monitoring stations throughout Scotland that generate data 24 hours a day. This hydrological information is combined with meteorological information from the Met Office.
	A team of experts then predict the likelihood and timing of river, coastal and surface water flooding.
	This joint initiative between SEPA and the Met Office forms the Scottish Flood Forecasting Service.
Flood frequency	The probability that a particular size/severity of flood will occur in a given year (see likelihood).
Flood gate	An adjustable, sometimes temporary, barrier used as a flood defence to control the flow of water within a water system or during a flood. Flood gates can also be part of operational flood defences or protect
	individual buildings or sites.
Flood guard	Flood guards cover a variety of types of door and window barriers that can be fitted to individual properties and operated by the owners / occupiers prior to a flood event.
	They act as a physical barrier to water entering the property and can provide protection against frequent and relatively shallow flooding.

Flood hazard	In terms of the Flood Risk Management Act, hazard refers to the characteristics (extent, depth, velocity) of a flood.
Flood hazard map	Flood hazard maps are required by the Flood Risk Management Act to show information that describes the nature of a flood in terms of the source, extent, water level or depth and, where appropriate, velocity of water.
	Flood hazard and risk maps are referred to collectively as flood maps and are available on the SEPA website.
Flood Prevention Scheme / Flood Protection Scheme (FPS)	A flood protection scheme, as defined by the Flood Risk Management Act, is a scheme by a local authority for the management of flood risk within the authority area.
	This includes defence measures (flood prevention schemes) formerly promoted under the Flood Prevention (Scotland) Act 1961.
Flood Prevention (Scotland) Act 1961	The Flood Prevention (Scotland) Act 1961 gave local authorities discretionary powers to make and build flood prevention schemes.
	It was superseded by the Flood Risk Management (Scotland) Act 2009.
Flood protection study	Flood protection studies aim to refine understanding of the hazard and risk associated with flooding in a particular area, catchment or coastline.
	They will involve detailed assessment of flood hazard and / or risk and may develop options for managing flood risk.
Flood protection works	Flood protection works can include the same flood defence measures that would make up a formal Flood Protection Scheme but without the legal process, protections and requirements that would come by delivering the works as a scheme.

Flood wiels	A
Flood risk	A measure of the combination of the likelihood of flooding occurring and the associated impacts on people, the economy and the environment.
Flood Risk Assessment	Flood Risk Assessments are detailed studies of an area where flood risk may be present.
	These are often used to inform planning decisions, may help to develop flood schemes and have also contributed to the National Flood Risk Assessment.
Flood Risk Management (Scotland) Act 2009 (FRM Act)	The flood risk management legislation for Scotland.
	It transposes the EC Floods Directive into Scots Law and aims to reduce the adverse consequences of flooding on communities, the environment, cultural heritage and economic activity.
Flood risk management cycle	Under the Flood Risk Management Act, flood risk management planning is undertaken in six year cycles.
	The first planning cycle is 2015-2021. The first delivery cycle is lagged by approximately 6 months and is from 2016-2022.
Flood Risk Management Local Advisory Groups	Flood risk management local advisory groups are stakeholder groups convened to advise SEPA and lead local authorities in the preparation of flood risk management plans.
	SEPA and lead local authorities must have regard to the advice they provide.
Flood Risk Management Plan (FRM Plans)	A term used in the Flood Risk Management Act.
	Flood risk management plans set out a long-term vision for the overall management of flood risk.
	They contain a summary of flood risk in each Local Plan District, together with information on catchment characteristics and a summary of

	objectives and actions within Potentially Vulnerable Areas.
Flood Risk Management Strategy (FRM Strategy)	The term used for the first set of flood risk management plans, which were published in December 2015.
	These are now referred to as the flood risk management plans to keep consistency with the Flood Risk Management Act and other areas of the UK.
Flood risk map	Complements the flood hazard maps published on the SEPA website providing detail on the impacts of flooding on people, the economy and the environment. Flood hazard and risk maps are referred to collectively as flood maps and are
Flood wall	A flood defence feature used to defend an area from flood water to a specified standard of protection.
Flood Warning Target Area (FWTA)	A Flood Warning target area is where SEPA operates a formal Flood Monitoring Scheme to issue targeted flood warning messages for properties located in the area.
Flood warning scheme	A flood warning scheme is the network of monitoring on a coastal stretch or river, which provides SEPA with the ability to issue flood warnings.
Floods directive	European Directive 2007/60/EC on the Assessment and Management of Flood Risks builds on and is closely related to the Water Framework Directive (see river basin management planning). It was transposed into Scots Law by the Flood Risk Management (Scotland) Act 2009.
	The Directive requires Member States to assess if all watercourses and coastlines are at risk from flooding, to map the flood extent, assets and humans at risk in these areas and to

	take adequate and co-ordinated measures to reduce this flood risk.
Floodplain	Area of land that borders a watercourse, an estuary or the sea, over which water flows in time of flood, or would flow but for the presence of flood defences and other structures where they exist.
Floodplain storage	Floodplains naturally store water during high flows. Storage can be increased through natural or man-made features to increase flood depth or slow flows in
Fluvial flooding	order to reduce flooding elsewhere. Flooding from a river or other watercourse.
Gabion	A metal cage filled with rocks often used in riverbank protection.
Green infrastructure	The European Commission defines green infrastructure as "the use of
	ecosystems, green spaces and water in strategic land use planning to deliver environmental and quality of life benefits.
	It includes parks, open spaces, playing fields, woodlands, wetlands, road verges, allotments and private gardens.
	Green infrastructure can contribute to climate change mitigation and adaptation, natural disaster risk mitigation, protection against flooding and erosion as well as biodiversity conservation."
	Also see 'blue infrastructure'.
Groundwater flooding	This type of flooding is caused by water rising up from underlying rocks or flowing from springs. In Scotland groundwater is generally a contributing factor to flooding rather than the primary source.
Integrated catchment study (ICS)	In urban areas, the causes of flooding are complex because of the interactions

	between rivers, surface water drainage and combined sewer systems and tidal waters. Scottish Water works with SEPA and local authorities to assess these interactions through detailed studies.
Land use planning (LUP)	The process undertaken by public authorities to identify, evaluate and decide on different options for the use of land, including consideration of long-term economic, social and environmental objectives and the implications for different communities and interest groups.
Lead local authority	A local authority responsible for leading the production, consultation, publication and review of a local flood risk management plan.
Likelihood of flooding	The chance of flooding occurring. High likelihood: A flood event is likely in the defined area on average once in every ten years (1:10). Or a 10% chance of happening in any one year. Medium likelihood: A flood event is likely in the defined area on average once in every two hundred years (1:200). Or a 0.5% chance of happening in any one year. Low likelihood: A flood event is likely in the defined area on average once in every thousand years (1:1000). Or a 0.1% chance of happening in any one year.
Local Flood Risk Management Plans (Local FRM Plan)	Local flood risk management plans, produced by lead local authorities, will take forward the objectives and actions set out in flood risk management plans. They will provide detail on the funding, timeline of delivery, arrangements and co-ordination of actions at the local level during each six-year, flood risk management planning cycle.
Local Nature Reserve (LNR)	A Local Nature Reserve is a protected area of land designated by a local authority because of its local special

	natural interest and / or educational
	value.
	Local authorities select and designate local nature reserves using their powers under the National Parks and Access to the Countryside Act 1949.
Local Plan District	Geographical areas for the purposes of flood risk management planning.
	There are 14 Local Plan Districts (LPDs) in Scotland.
Local Plan District Partnerships	Each LPD has established a local partnership comprised of local authorities, SEPA and Scottish Water and others as appropriate.
	These partnerships are distinct from the flood risk management plans local advisory groups and they retain clear responsibility for delivery of the flood risk management actions set out in the Local flood risk management plans.
	It is the local partnership that makes decisions and supports the delivery of these plans.
Maintenance	Sections 18 and 59 of the Flood Risk Management (Scotland) Act 2009 put duties of watercourse inspection, clearance and repair on local authorities.
	In addition, local authorities may also be responsible for maintenance of existing flood protection schemes or defences.
Montane habitat	This habitat encompasses a range of natural or near-natural vegetation occurring in the montane zone, lying above or beyond the natural tree-line.
National Flood Management Advisory Group (NFMAG)	The National Flood Management Advisory Group provides advice and support to SEPA and, where required, Scottish Water, local authorities and other responsible authorities on the production of flood risk management plans and Local flood risk management plans.

National Flood Risk Assessment (NFRA)	A national analysis of flood risk from all sources of flooding which also considers climate change impacts. First published in December 2011 this provides the information required to undertake a strategic approach to flood management that identifies areas at flood risk that require further appraisal. The NFRA was reviewed and updated for the second cycle of flood risk management planning in 2018.
Natural flood management (NFM)	A set of flood management techniques that aim to work with natural processes (or nature) to manage flood risk.
Non-residential properties	Properties that are not used for people to live in, such as shops or other public, commercial or industrial buildings.
Objectives	Objectives provide a common goal and shared ambition for managing floods.
	These objectives have been set by SEPA and agreed with flood risk management authorities following consultation.
	They were identified through an assessment of the underlying evidence of the causes and impacts of flooding.
One in 200 year flood	See 'likelihood of flooding' and 'return period'.
Options appraisal study	An options appraisal study looks to identify and assess a range of options that achieve flood risk management objectives whilst delivering other economic, social and environmental benefits.
	This helps to inform the decision-making process and identify how options work together to identify a preferred option for managing flooding within an area.
Planning policies	Current national planning policies, Scottish Planning Policy and accompanying Planning Advice notes

	restrict development within the floodplain and limit exposure of new receptors to flood risk. In addition to national policies, local planning policies may place further requirements within their area of operation to restrict inappropriate development and prevent unacceptable risk.
Potentially Vulnerable Areas (PVA)	Catchments identified as being at risk of flooding and where the impact of flooding is sufficient to justify further assessment and appraisal.
	There were 243 PVAs identified by SEPA in the 2011 National Flood Risk Assessment and were the focus of the first flood risk management planning cycle.
	There are 233 PVAs identified for the 2018 National Flood Risk Assessment.
Preferred option	A preferred option identifies the collection of flood management options which combined offer the most suitable way of managing flooding within an area. Based on the economic, social and environmental benefits of the options.
Property level protection	Property level protection includes flood gates, sandbags and other temporary barriers that can be used to prevent water from entering individual properties during a flood.
Property level protection scheme	Some responsible authorities may have a formal scheme to provide, install and maintain property level protection for properties.
Ramsar sites	Ramsar sites are wetlands of international importance designated under the Ramsar Convention.
Receptor	Refers to the entity that may be impacted by flooding (a person, property, infrastructure or habitat).

	The vulnerability of a receptor can be reduced by increasing its resilience to flooding.
Residual risk	The risk which remains after risk management and mitigation. This may include risk due to very severe (above design standard) storms or risks from unforeseen hazards.
Resilience	The ability of an individual, community or system to recover from flooding.
Responsible authority	Designated under the Flood Risk Management (Scotland) Act 2009 and associated legislation as local authorities, Scottish Water and, from 21 December 2013, the National Park Authorities and Forestry Commission Scotland.
	Responsible authorities, along with SEPA and Scottish Ministers, have specific duties in relation to their flood risk related functions.
Return period	A measure of the rarity of a flood event. It is the statistical average length of time separating flood events of a similar size. (See Likelihood).
Revetment	Sloping structures placed on banks or at the foot of cliffs in such a way as to deflect the energy of incoming water.
Riparian	The riparian area is the interface between land and a river or stream.
River basin management planning (RBMP)	The Water Environment and Water Services (Scotland) Act 2003 transposed the European Water Framework Directive into Scots law.
	The Act created the River Basin Management Planning process to achieve environmental improvements to protect and improve our water environment.
	It also provided the framework for regulations to control the negative

	impacts of all activities likely to have an impact on the water environment.
Runoff reduction	Actions within a catchment or sub- catchment to reduce the amount of runoff during rainfall events. This can include intercepting rainfall, storing water, diverting flows or encouraging infiltration.
Scottish Advisory and Implementation Forum for Flooding (SAIFF)	The stakeholder forum on flooding set up by the Scottish Government to ensure legislative and policy aims are met and to provide a platform for sharing expertise and developing common aspirations and approaches to reducing the impact of flooding on Scotland's communities, environment, cultural heritage and economy.
Sediment balance	Within a river where erosion and deposition processes are equal over the medium to long-term resulting in channel dimensions (width, depth, slope) that are relatively stable.
Sediment management	Sediment management covers a wide range of activities that includes anything from the small-scale removal of dry gravels to the dredging of whole river channels and the reintroduction of removed sediment into the water environment.
	Historically, sediment management has been carried out for several reasons, including reducing flood risk, reducing bank erosion, for use as aggregate and to improve land drainage.
Self help	Self help actions can be undertaken by any individuals, businesses, organisations or communities at risk of flooding.
	They are applicable to all sources, frequency and scales of flooding.
	They focus on awareness raising and understanding of flood risk.

Sewer flooding (and other artificial drainage system flooding)	Flooding as a result of the sewer or other artificial drainage system (e.g. road drainage) capacity being exceeded by rainfall runoff or when the drainage system cannot discharge water at the outfall due to high water levels (river and sea levels) in receiving waters.
Site protection plans	Site protection plans are developed to identify whether normal operation of a facility can be maintained during a flood. This may be due to existing protection or resilience of the facility or the network.
Shoreline Management Plan (SMP)	A Shoreline Management Plan is a large-scale assessment of the coastal flood and erosion risks to people and the developed, historic and natural environment.
	It sets out a long-term framework for the management of these risks in a sustainable manner.
Site of Special Scientific Interest (SSSI)	Sites of Special Scientific Interest are protected by law under the Nature Conservation (Scotland) Act 2004 to conserve their plants, animals and habitats, rocks and landforms.
Source of flooding	The type of flooding. This can be coastal, river, surface water or groundwater.
Special Area of Conservation (SAC)	Special Areas of Conservation are strictly protected sites designated under the European Habitats Directive.
	The Directive requires the establishment of a European network of protected areas which are internationally important for threatened habitats and species.
Special Protection Areas (SPA)	Special Protection Areas are strictly protected sites classified in accordance with the European Birds Directive.
	They are classified for rare and vulnerable birds (as listed in the

	Directive), and for regularly occurring migratory species.
Standard of protection (SoP)	All flood protection structures are designed to be effective up to a specified flood likelihood (Standard of Protection).
	For events beyond this standard, flooding will occur. The chosen Standard of Protection will determine the required defence height and / or capacity.
Storage area	A feature that can be used to store floodwater, this can be natural in the form of low-lying land or manmade such as a reservoir or modified landform.
Strategic Environmental Assessment (SEA)	A process for the early identification and assessment of the likely significant environmental effects, positive and negative, of activities. Often considered before actions are approved or adopted.
Strategic Flood Risk Assessment (SFRA)	A Strategic Flood Risk Assessment is designed for the purposes of specifically informing the Development Plan Process.
	A SFRA involves the collection, analysis and presentation of all existing and readily available flood risk information (from any source) for the area of interest.
	It constitutes a strategic overview of flood risk.
Strategic mapping improvements	Strategic mapping improvement actions have been identified in locations where SEPA is planning to undertake additional modelling or analysis of catchments and coastlines, working collaboratively with local authorities where appropriate, to improve the national understanding of flood risk.
Surcharge	Watercourses and culverts can carry a limited amount of water. When they can no longer cope, they overflow, or 'surcharge'.

Surface water flooding	Flooding that occurs when rainwater does not drain away through the normal drainage systems or soak into the ground, but lies on or flows over the ground instead.
Surface Water Management Plan (SWMP)	A plan that takes an integrated approach to drainage accounting for all aspects of urban drainage systems and produces long term and sustainable actions.
	The aim is to ensure that during a flood the flows created can be managed in a way that will cause minimum harm to people, buildings, the environment and business.
Surface water plan / study	The management of flooding from surface water sewers, drains, small watercourses and ditches that occurs, primarily in urban areas, during heavy rainfall.
	Flood risk management plan actions in this category include: Surface Water Management Plans, Integrated Catchment Studies and assessment of flood risk from sewerage systems (Flood Risk Management Act, Section 16) by Scottish Water. These have been selected as appropriate for each Potentially Vulnerable Area.
Sustainable flood risk management	The sustainable flood risk management approach aims to meet human needs, whilst preserving the environment so that these needs can be met not only in the present, but also for future generations.
	The delivery of sustainable development is generally recognised to reconcile three pillars of sustainability – environmental, social and economic.
Sustainable drainage systems (SuDS)	A set of techniques designed to slow the flow of water.
	They can contribute to reducing flood risk by absorbing some of the initial rainfall and then releasing it gradually,

	thereby reducing the flood peak and helping to mitigate downstream problems. SuDS encourage us to take account of quality, quantity and amenity / biodiversity.
Target area	Target areas are based on communities at risk of flooding.
	These are situated within Potentially Vulnerable Areas and should benefit from actions to reduce flood risk.
	To benefit the community, actions may apply to outside the target area.
	National flood risk management efforts and funding should be targeted to benefit these target areas.
UK Climate Change Projections (UKCP18)	The leading source of climate change information for the UK. It can help users to assess their climate risks and plan how to adapt to a changing climate. The high emissions scenario refers to
	the RCP8.5emission scenario. See the UKCP18 climate change projections report for details.
Utility assets	Within the flood risk management plans this refers to electricity sub stations, mineral and fuel extraction sites, telephone assets, television and radio assets.
Voe	A dialect term, common in place names and used to refer to a small bay or creek in Orkney or Shetland.
Vulnerability	A measure of how likely someone or something is to suffer long-term damage as a result of flooding.
	It is a combination of the likelihood of suffering harm or damage during a flood (susceptibility) and the ability to recover following a flood (resilience).
Wave energy dissipation	Process by which a wave loses its energy.

Wave overtopping	Wave overtopping occurs when water passes over a flood wall or other structure as a result of wave action.
	Wave overtopping may lead to flooding particularly in exposed coastal locations.